

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A double belt transport system having an upstream end and a downstream end for moving a mailpiece from the upstream end into a printing area of a printer, wherein the mailpiece has a lower surface and an opposing upper surface to be printed by a print head located in the printing area, said transport system comprising:

an upper looping belt having a straight section with a predetermined width ~~[covering]~~adjacent the printing area, wherein the straight section defines a registration plane regarding the print head; and

a lower looping belt having an upper span that contacts the straight section of the upper belt forming mailpiece intake section that extends beyond the width of the upper belt adjacent the printing area running from the upstream end towards the downstream end, wherein the mailpiece intake section and the straight section form a wedge-shaped gap resulting in a soft ingest nip for receiving a mailpiece at the upstream end so that the tension of the lower belt is controlled by the elasticity of the lower belt wrapped around fixed pulleys to provide a normal force between mailpieces having different thicknesses and the upper belt for providing a friction force to move the mailpiece into the printing area for printing.

2. (original) The double belt transport system of claim 1, further comprising a lifting mechanism located below the lower surface of the mailpiece for urging the mailpiece to move towards the straight section of the upper looping belt so that the upper surface of the mailpiece is located substantially in the registration plane when the mailpiece is moving into the printing area.

3. (original) The double belt transport system of claim 2, further comprising a shield plate having a reference surface facing the lifting mechanism and located substantially in the registration plane in the printing area so as to allow the upper surface of the mailpiece to press against the reference surface for registration when the mailpiece is urged by the lifting mechanism to move towards the upper looping belt when the mailpiece is moving into the printing area.

4. (original) The double belt transport system of claim 1, further comprising an upstream pulley and a downstream pulley defining a tangent plane therebetween, wherein the tangent plane is substantially parallel to the registration plane, and wherein the upstream and downstream pulleys push against the upper looping belt to define the straight section of the upper looping belt.

5. (original) The double belt transport system of claim 1, further comprising a deck having an upstream section located adjacent to the intake nip for supporting the mailpiece when the mailpiece moves towards the ingest nip.

6. (original) The double belt transport system of claim 1, further comprising means for driving the upper looping belt and the lower looping belt for reducing shearing on the mailpiece.

7. (original) The double belt transport system of claim 1, further comprising a velocity measurement mechanism operatively connected to at least one of the looping belts so as to match the printing speed of the print head to moving speed of the mailpiece in the printing area.

8. (original) The double belt transport system of claim 1, wherein the print head comprises a plurality of inkjet nozzles for printing.

9. (Cancel)

10. (Cancel)

11. (currently amended) A printer having an upstream end and a downstream end for printing a mailpiece on an upper surface thereof, said printer comprising:

 a print head located above a printing area; and

 a double belt transport system for moving the mailpiece from the upstream end into the printing area, wherein the mailpiece has a lower surface opposing the upper surface, and wherein the double belt transport system comprises:

an upper looping belt having a straight section covering the printing area, wherein the straight section defines a registration plane regarding the print head; and

a lower looping belt having an upper span that contacts the straight section of the upper belt forming ~~mailpiece intake section running from the upstream end towards the downstream end, wherein the mailpiece intake section and the straight section form a wedge-shaped gap resulting in a soft ingest nip so~~ that the tension of the lower belt provides a normal force between the mailpiece and the upper belt for providing a friction force to move the mailpiece into the printing area for printing.

12. (original) The printer of claim 11, further comprising a lifting mechanism located below the lower surface of the mailpiece for urging the mailpiece to move towards the straight section of the upper looping belt so that the upper surface of the mailpiece is located substantially in the registration plane when the mailpiece is moving into the printing area.

13. (original) The printer of claim 12, further comprising a shield plate having a reference surface facing the lifting mechanism and located substantially in the registration plane in the printing area so as to allow the upper surface of the mailpiece to press against the reference surface for registration when the mailpiece is urged by the lifting mechanism to move towards the upper looping belt when the mailpiece is moving into the printing area.

14. (original) The printer of claim 11, further comprising an upstream pulley and a downstream pulley defining a tangent plane therebetween, wherein the tangent plane is substantially parallel to the registration plane and wherein the upstream and downstream pulleys push against the upper looping belt to define the straight section of the upper looping belt.

15. (original) The printer of claim 11, further comprising a deck having an upstream section located adjacent to the intake nip for supporting the mailpiece when the mailpiece moves towards the ingest nip.

16. (original) The printer of claim 11, further comprising means for driving the upper looping belt and the lower looping belt for reducing shearing on the mailpiece.

17. (previously presented) The printer of claim 11, further comprising a velocity measurement mechanism operatively connected to at least one of the looping belts so as to match printing speed of the print head to moving speed of the mailpiece in the printing area.

18. (original) The system claimed in claim 1, further including:
 a tensioning idler to maintain tension for the lower belt.

19. (original) The method claimed in claim 9, wherein the tension of the lower belt is maintained by a tensioning idler.

20. (original) The printer claimed in claim 11, further comprising:
 a tensioning idler to maintain tension for the lower belt.
21. (new) The printer claimed in claim 11, wherein the lower belt is wide than the
upper belt to allow registration of the mail piece in the printing area.
22. (new) The printer claimed in claim 11, wherein the lower belt comprises: a first
lower belt and a second lower belt located inbound of the printing area wherein the first
and second lower belt support the mail piece on areas adjacent the print head.